ACCUTRAK - CORROSION MAPPING





Modular design



Axial Scanning -Laser guided



3-Axis - Remote corrosion mapping



2-Axis - Weld exams / Line B-Scans

ightarrow TECHNICAL SPECIFICATION STANDARD KIT

| | ACCUTRAK CORROSION BSCAN | ACCUTRAK WELD INSPECTION | ACCUTRAK CORROSION MAPPING |
|---------------------------|---|---|--|
| Thickness measurement | \checkmark | \checkmark | \checkmark |
| Weld inspection | | ✓ | ✓ |
| Corrosion mapping | | | ✓ |
| Dimensions (L x W x H) | 13.5 x 10.5 x 4.25″ 33 x 25 x 10 cm | 13.5 x 10.5 x 4.25″ 33 x 25 x 10 cm | 13.5 x 10.5 x 4.25″ 33 x 25 x 10 cm |
| X-axis Encoder resolution | X: 42725.56 ticks /i n (1682 ticks / mm) | X: 42725.56 ticks / in (1682 ticks / mm) | X: 42725.56 ticks / in (1682 ticks / mm) |
| Y-axis Encoder resolution | - | - | Y: 6666.67 ticks / in (262.47 ticks / mm) |
| Scan speed | X-axis : 6"/ s (150 mm / s) | X-axis : 6"/ s (150 mm / s) | X-axis : 6″/s (150 mm / s) Y-axis : 30″/s (762mm / s) |
| 2-axis inspection | \checkmark | \checkmark | \checkmark |
| 3rd axis arm with motor | - | - | \checkmark |
| Circumferential OD | From 4" / 10 cm | From 4" / 10 cm | From 4" / 10 cm |
| Axial OD | From 8" / 20 cm | From 8" / 20 cm | From 8" / 20 cm |
| Spiral weld OD | From 24" / 61 cm | From 24" / 61 cm | From 24" / 61 cm |
| Turn radius | 12″/ 30,5 cm | 12″/ 30,5 cm | 12″/ 30,5 cm |
| Joystick | √ | √ | 1 |
| Umbilical default length | 100 ft. / 30 m | 100 ft. / 30 m | 100 ft. / 30 m |
| Travel case dimensions | 32 x 21 x 16″ | 32 x 21 x 16″ | 32 x 21 x 16″ |

ightarrow options

| | ACCUTRAK CORROSION BSCAN | ACCUTRAK WELD INSPECTION | ACCUTRAK CORROSION MAPPING |
|--|-----------------------------|-----------------------------|-------------------------------|
| Battery autonomy | 8 hours | 8 hours | 8 hours |
| Spare motors kit (X & Y) | \checkmark | \checkmark | \checkmark |
| 12, 24, 36 and 48" arms | - | \checkmark | \checkmark |
| Rechargeable battery pack with charger | \checkmark | ✓ | \checkmark |
| Catamaran kit | - | \checkmark | - |
| Fixed probe | \checkmark | - | \checkmark |
| 50 - 200 feet umbilicals | \checkmark | \checkmark | \checkmark |
| Multi-probe kit for TOFD and PAUT probes | \checkmark | ✓ | \checkmark |
| Laser line - green (battery powered) | - | \checkmark | - |
| Camera 45 ft, USB | \checkmark | \checkmark | \checkmark |
| Truck extension for ID scanning of 14" pipe | \checkmark | ✓ | √ |
| ProScan XT Single Channel 2 axis encoding | \checkmark | - | \checkmark |

Features

A

- Steerable automated scanner up to 3-axis
- Modular design adaptable to various environment and applications
- Fast inspection X: 6"/sec Y: 30"/sec
- Lightweight less than 17 Lbs / 8 kg
- Reliable 11 years presence in the field, 200+ units in use
- Technology UT, PAUT, EMAT, RVT
- Robust strong magnetic wheels allowing vertical climbing



Scan to find out more about AccuTrak